

FORMEX, DIV OF ILLINOIS TOOL WORKS INC., FORMERLY

FASTEX, DIV OF ILLINOIS TOOL WORKS INC 1701 W ARMITAGE CT ADDISON IL 60101

Material Designation: **FORMEX** -(a)(b)(f2)@

Product Description: Polypropylene (PP), furnished as sheets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
NC	0.20	VTM-0	5	1	95	-	95	-	-
	0.41	V-0	4	3	100	90	100	-	-
ALL	0.75	V-0	3	0	110	105	110	-	-
	2.4	V-0	2	0	110	105	110	-	-
	3.0	V-0	2	0	110	115	120	-	-
CTI: 0			HVTR: 0		D495: 6		IEC BP: -		

(a) - One to three digit suffix indicating nominal thickness in mils.

(b) - May have an additional letter suffix indicating color.

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL Inc.

@ - HVTR, D495 and CTI are thickness independent.

FORMEX, DIV OF ILLINOIS TOOL WORKS INC., FORMERLY

FASTEX, DIV OF ILLINOIS TOOL WORKS INC 1701 W ARMITAGE CT ADDISON IL 60101

Material Designation: **FORMEX GK - (a)(b)(f2)@**

Product Description: Polypropylene (PP), furnished as sheets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	0.05	VTM-0	4	0	115	-	115	-	-
	0.10	VTM-0	4	0	115	-	115	-	-
	0.20	VTM-0	4	0	115	-	115	-	-
	0.41	V-0	4	0	115	-	115	-	-
	0.71	V-0	4	0	115	-	115	-	-
	3.0	V-0	1	0	115	-	115	-	-
CTI: 0			HVTR: 0		D495: 6		IEC BP: -		

(a) - One to three digit suffix indicating nominal thickness in mils.

(b) - May have an additional letter suffix indicating color.

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL Inc.

@ - HVTR, D495 and CTI are thickness independent.

Report Date: 08/19/1991

Underwriters Laboratories Inc®

136340001

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.

FORMEX, DIV OF ILLINOIS TOOL WORKS INC., FORMERLY

FASTEX, DIV OF ILLINOIS TOOL WORKS INC 1701 W ARMITAGE CT ADDISON IL 60101

Material Designation: **STATEX-(a)(b)(f2)@**

Product Description: Polypropylene (PP), static dissipative treated, furnished as sheets.

Color	Min. Thck. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
NC	0.20	VTM-0	5	1	95	-	95	-	-
	0.41	V-0	4	3	100	90	100	-	-
ALL	0.75	V-0	3	0	110	105	110	-	-
	2.4	V-0	2	0	110	105	110	-	-
	3.0	V-0	2	0	110	115	120	-	-
CTI: 0			HVTR: 0		D495: 6		IEC BP: -		

(a) - One to three digit suffix indicating nominal thickness in mils.

(b) - May have an additional letter suffix indicating color.

(f2) - Subjected to one or more of the following tests: Ultraviolet Light, Water Exposure or Immersion in accordance with UL 746C, where the acceptability for outdoor use is to be determined by UL Inc.

@ - HVTR, D495 and CTI are thickness independent.

Report Date: 08/19/1991

Underwriters Laboratories Inc®

136340001

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.